

The SPU61A series of AC/DC switching mode power supplies provide 60 Watts of continuous output power. All supplies are UL 94V-1 min compliant. All models meet FCC Part-15 class B and CISPR-22 class B emission Limits and are designed to comply with UL/c-UL, TUV/GS and CE marking conformity assessment. All units are 100% burned in and tested.



**RoHS2**  
2011/65/EU

#### FEATURES:

- \* Wide Operating Voltage 90 to 264 VAC, 47 to 63 Hz
- \* IEC-320-C14 Input Inlet
- \* Other Input/Output Configurations Available (contact Beta Dyne Sales)
- \* Single Output (Factory set, contact Beta Dyne Sales for other Voltage options)
- \* Approved as Limited Power Source (LPS)
- \* DoE VI
- \* 3 year warranty

#### APPLICATIONS:

- \* POS System AV Equipment
- \* Industrial PC
- \* Note PC
- \* Charger
- \* LED Lighting

#### GENERAL SPECIFICATION:

- \* **Short Circuit Protection:** Auto Recovery
- \* **Cooling:** Free Air Convection
- \* **Flammability Rating:** UL94V-1
- \* **Protection Classes:** Class I
- \* **Safety:** UL 60950-1:2nd Edition, IEC 60950-1:2005 /A2:2013, EN60950-1:2006 /A2:2013

#### APPROVALS:



#### Electrical Characteristics:

Symbol	Characteristic	Condition	Min.	Typ.	Max.	Unit
Vins	Safety Approval Input Voltage Range	Safety Approval & Specification in Label	100		240	VAC
Vin	Input Operate Voltage Range	Detail to see Fig.1	90		264	VAC
Fi	Input Frequency	Sine wave	47		63	Hz
Po	Output Power Range	See Rating Chart			60	W
Iil	Low Line Input Current	Full Load, Vin=100VAC			1.45	A
Iih	High Line Input Current	Full Load, Vin=240VAC			1.45	A
Irh	High Line Input Inrush Current	Full Load, 25°C, Cool start, Vin=240VAC			105	A
Ik	Safety Ground Leakage Current	Vin=240VAC, Fi=60Hz			0.75	mA
η	Efficiency	Full Load, Vin=230VAC, Detail to see Rating Chart	See Rating Chart			
ΔVoi	Line Regulation	Full Load, Vin=100~120VAC	0.5		1	%
ΔVoL	Load Regulation	Vin=230VAC, 10~90% Load Change at Condition	3		5	%
OLP	Over Load Protection	Recovers automatically after fault condition is removed	110		150	%
ttr	Time of Transient Response	Full Load, Vin=110VAC			4	ms
thu	Hold-Up Time	Full Load, Vin=100VAC	See Rating Chart			
ts	Start-up time	Full Load, Vin=100~240VAC			3	s
Tc	Temperature Coefficient	Full load, Vin=100~240VAC			±0.04	%/°C
HV	Dielectric Withstanding Voltage (P-S)	Primary to Secondary			4242	VDC
Vpg	Dielectric Withstanding Voltage (P-G)	Primary to PE			2652	VDC
EMI	EMC Emission	Compliance to EN55022 (CISPR22)			B	Class

#### Environmental:



Symbol	Characteristic	Condition	Min.	Typ.	Max.	Unit
To	Operating Temperature	Detail to see Fig.2 (Derate linearly from 100% load at 40°C to 50% load at 70°C)	0		70	°C
Ts	Storage Temperature	10 ~ 95% RH	-40		85	°C
Ho	Operating Humidity	non-condensing	0		95%	RH
Hs	Storage Humidity		0		95%	RH
ESDa	Electro Static Discharge	Air Discharge, IEC61000-4-2			8	kV
ESDc	Electro Static Discharge	Contact Discharge, IEC61000-4-2			6	kV
MTBF	Mean Time Between Failure	Operating Temperature at 25°C, Calculated per MIL-HDBK-217F	100k			h
ELEV	Operating Altitude (Elevation)	All condition			2000	m
VBR	Vibration	10 ~ 500Hz, 10min./1cycle, 60min. each along X, Y, Z axes			5	G
Vsl	Surge Voltage	Line-Neutral			1	kV
Vsg	Surge Voltage	Line-PE & Neutral-PE			2	kV

**SPECIFICATION NOTE :**


1. Output can provide up to peak load when the power supply starts up. Continuous staying in more than rated load is not allowed.
2. At factory, in 60% rated load condition, each output is checked to be within voltage accuracy.
3. Line regulation is defined by changing  $\pm 10\%$  of input voltage from nominal line at rated load.
4. Load regulation is defined by changing  $\pm 40\%$  of measured output load from 60% rated load.
5. Ripple & noise is measured by using 20MHz bandwidth limited oscilloscope and terminated each output with a 0.47uF capacitor at rated load and nominal line.
6. Hold up time is measured from the end of the last charging pulse to the time which the main output drops down to low limit of main output at rated load and nominal line.
7. Efficiency is measured at rated load, and nominal line.

**MECHANICAL DIMENSIONS: ( UNIT: mm )**

Input Cord Not Included, Contact Beta Dyne Sales



(FIG.1) INPUT VOLTAGE DERATING CURVE



(FIG.2) TEMPERATURE DERATING CURVE

**OUTPUT CABLE DETAILS :**

1. SPU61A-105 is required to use AWG#16 / 4FT output cable.
2. SPU61A-106~111 are required to use AWG#18 / 4FT output cable.
3. The regulation and efficiency will be changed by modifying the output cable.

**PACKING :**

Net weight: 340g approx.

**Rating Chart:**

MODEL NO.	Output Voltage (Factory set, can't be adjusted. Contact Beta Dyne Sales for other options)	Output Current	Maximum Output Power	Ripple & Noise	Total Regulation	Typ. Efficiency	Typ. No Load Consumption	Hold-Up Time	Protection Mode
	(VDC)								
SPU61A-105	12.0	5.00	60	100	$\pm 5$	87.7	0.21	10	Hiccup
SPU61A-106	15.0	4.00	60	100	$\pm 5$	87.7	0.21	10	Hiccup
SPU61A-107	18.0	3.33	60	100	$\pm 5$	87.7	0.21	10	Hiccup
SPU61A-108	24.0	2.50	60	100	$\pm 3$	88	0.21	10	Hiccup
SPU61A-109	30.0	2.00	60	100	$\pm 3$	88	0.21	10	Hiccup
SPU61A-110	36.0	1.66	60	100	$\pm 3$	88	0.21	10	Hiccup
SPU61A-111	48.0	1.25	60	100	$\pm 3$	88	0.21	10	Hiccup

\*SPU61A-105~111 are CoC V5 tier2 model available, please contact sales.